# JATHEON

DATA | KNOWLEDGE | INSIGHT

Model	cCore 12
Storage Capacity	12TB (RAIDZI)
Available Storage:	8TB



Core 12

# DATA SHEET

#### System:

Processors: Intel Xeon E3-1220V3 3.1 8M cache (4x cores/ 4x threads) Memory: 32 Gb ECC (max 32 Gb) Chipset: Intel C222/C244 Network Controllers: 4 x 1000BASE Gbit Ethernet IPMI Interface

#### Chassis:

Form factor: 1U rackmount Dimensions: 437mm(W) × 43mm(H) × 503mm(D) Cooling system: 4x 4cm 12.5K RPM PWIM fans

Today's successful corporations find more than 75% of their intellectual property stored in emails, which explains their need for a secure and powerful email data management tool.

Jatheon's cCorel2 appliance is the perfect fit: it easily handles high data flow, monitors, indexes and securely stores all emails on the fly and lets users intelligently manage and retrieve information instantly – for compliance, eDiscovery, business management and more. cCorel2 combines the essential on-premise security you want, with the smart control over your data you need.

# FEATURES

- Remote System Monitoring
- ✓ Full Indexing & Archiving
- ✓ Message Compression
- ✓ Single Instance Storage
- ✓ Search & Retrieval
- ✓ Retention Policy
- Management
- ✓ Legal Hold
- ✓ Role Based Administration
- ✓ Outlook Plugin
- ✓ Tamper Proof OS & Storage
- ✓ Comprehensive Audit Trail
- ✓ Web Based Interface
- Comprehensive Reporting & Statistics

Storage: SSD: 1 × 120GB SATA III 2.5'' SAS: 4 × 3TB 6.0Gbps 3.5'' 128MB cache 7200RPM (hot swap) RAID: RAIDZ1

### ZFS:

Self-healing Auto Bit Rot Recovery Unlimited file system snapshots for archive protection and backups Super efficient file system replication Data Integrity Verification Protection Against Data Corruption

#### Graphics: Intel HD Graphics

#### Front Panel:

Power On/Off button System Reset button Power LED Hard drive activity LED 2x Network activity LEDs System Overheat LED 2x Front USB Ports Ix Serial COM Port

Back Plane:

I x SAS / SATA Backplane

#### Power Supply:

350W AC power supply w/ PFC AC Voltage: 100-240 V, 50-60 Hz, 4.2-1.8 Amp +5V: 18 Amp +5V Standby: 3 Amp +12V: 29 Amp +3.3V: 15 Amp

#### Operating Environment / Compliance:

USA - UL listed, FCC Canada - CUL listed Europe/CE Mark EN 60950/IEC 60950-Compliant

Shipping Weight: 42 lb